



## Half Heights

BK2 is an IMDG (International Maritime Dangerous Goods) code that redefines Bulk Containers. It differs from standard ISO in two main areas:

- End wall strength is greater, with test load of 0.6 payload, compared to 0.4 for a standard ISO container.
- Loose bulk must be contained without leakage.

<b>External dimensions</b>	6m x 2.43m x 1.45m (high), 20' x 8' x 4' 9" (high)
<b>Internal dimensions</b>	5.8m x 2.37m x 1.40m, 19'10" x 7' 10" x 4' 7"
<b>Cubic capacity</b>	15.5 m <sup>3</sup> 547 ft <sup>3</sup>
<b>Maximum gross weight</b>	33,000 kgs, 72,750 lbs
<b>Tare weight</b>	3,150 kgs, 6,940 lbs
<b>Maximum payload</b>	29,850 kgs, 65,810 lbs
<b>Discharge type</b>	Tipping or Rotational
<b>Structure</b>	Steel or aluminium exterior, stainless steel interior
<b>Door locking gear</b>	4 sets including provision for seals and padlocks



- Built for heavy bulk loads not requiring large cubic capacity
- Suitable for diverse cargo types
- Ideal for dense cargos transported by the mining and mineral by-product industries

**All specifications are indicative. Individual container dimensions may differ.**

Lease or purchase

sales@cargostore.com  
 0208 879 1900 | www.cargostore.com